Date Revised: February 1, 2006

Section I. Product Identification

Product Name: Barium Sulfate Suspension Products Manufacturer: E-Z-EM, Canada, on behalf of E-Z-EM, Inc., 1111 Marcus Avenue, Suite LL-26, Lake Success, New York, 11042. Emergency/Information Contact: Adrianne Setton

Emergency/Information Telephone: (800)-544-4624 or (516) 333-8230, extension 3400 Product Codes: 720,721,723,724,726,728,729,738,770,7150, 7250,7350,7450,7550, 7650, 8140,9450,

L147,L150,L164,L168,L178, L186,L196,P410,P650PPS

Section II. Components

Components	CAS No.	%(Optional)
Barium Sulfate (can contain silica)	7727-43-7 (14808-60-7)	Proprietary (0.1 - 1% of barium sulfate)
Suspending and Dispersing Agents		Proprietary
Flavors		Proprietary
May contain Sorbitol	50-70-4	Proprietary
May contain Poligeenan	53973-98-1	>0.1%
May contain Sodium Saccharin	128-44-9	<0.1%

Section III. Physical Data

Boiling Point: Not tested Specific Gravity (H₂O = 1): Range : Not tested Vapor Pressure (mm Hg): Not tested Melting Point: Not tested Vapor Density (Air = 1): Not tested Evaporation Rate (Butyl Acetate = 1): Not tested Solubility in Water: Insoluble Appearance & Odor: White to off-white or tan suspension with no odor or slightly fruity or vanillin odor.

Section IV. Fire and Explosion Hazard Data

Flash Point (method): Not tested Flammable Limits: UEL - N/A LEL - N/A Fire Extinguishing Media: Use extinguishing media that is suitable for surrounding fire. Special Fire Fighting Procedures: Firefighters should wear full protective equipment and self- contained breathing apparatus with full face piece. Unusual Fire & Explosion Hazards: None known Toxic Gases Emitted: Sulfur dioxide

Section V. Reactivity Data

Stability: Stable Conditions to avoid: None documented Incompatible materials: Phosphorus, Aluminum Decomposition products: Not tested Hazardous Polymerization: Will not occur

Section VI. Health Hazard Data

Permissible Exposure Limit (PEL) for barium sulfate: Total Dust - 15 mg/m³ Time Weighted Average (TWA), Respirable dust - 5 mg/m³ TWA. Dust is not a concern since these products are liquids. **Threshold Limit Value (TLV) for barium sulfate:** Total Dust: 10 mg/m³ TWA Silica - quartz, respirable dust - 0.1 mg/m³. Dust is not a concern since these products are liquids. **Short-Term Exposure Limit (STEL):** Not established **Routes of Exposure:** Inhalation (dust exposure is not a concern since these products are liquids), Ingestion **Health Hazards (acute and chronic):** Through normal routes of entry, not expected to be a hazard. In some cases where skin and eye contact occurs, product may cause irritation. No adverse health effects expected from chronic exposure.

Carcinogenicity: Some products contain poligeenan. IARC lists poligeenan as a Class 2B meaning it is Apossibly carcinogenic to humans. **NTP:** No **IARC:** Yes **OSHA:** No

Effects of exposure: May cause constipation. Some formulations contain sorbitol, which may cause diarrhea in some individuals. Consult label for more information.

Medical conditions generally aggravated by exposure: No information found relating to normal routes of exposure.

Emergency and First Aid procedures:

- Eye contact Flush with water for at least 15 minutes.
- Skin contact Wash area thoroughly with soap and water.
- If ingested and person is conscious Give several glasses of water to dilute. If irritation persists or large quantities are ingested, get medical attention.

Section VII. Spill and Disposal Information

Steps to be taken in case material is released or spilled: Wear appropriate protective equipment. Absorb material with an absorbent and inert material, such as sand or vermiculite. Place materials in a container and label properly.

Waste Disposal Procedures: Products are not listed hazardous wastes under RCRA. Products are not likely to qualify as characteristic hazardous wastes, but any final determination depends on the specific circumstances of product usage and handling. Disposal should take place in compliance with federal, state and local laws and regulations.

Section VIII. Handling and Storage Precautions

- Store indoors in a tightly closed container, protected from extreme temperatures and potential sources of damage. Can be stored in any general chemical storage area.
- Do not smoke, eat or drink while handling any chemical. Practice good industrial and personal hygiene to avoid unnecessary exposure.

Section IX. Protective Equipment

Respiratory Protection: Barium sulfate liquid suspensions are not expected to require any personal respirator usage. Ventilation: Use adequate local exhaust ventilation to keep fume levels as low as possible. Protective Gloves: Appropriate gloves Eye Protection: Safety goggles or glasses Emergency Equipment: Always ensure there is an emergency eye wash in the area.