

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

078939104

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

078939037 078939040 078939042 078939045 078939102 078939106 078939108 078939109 078939110 078939114

078939115 078939116



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### Section 1 - Chemical Product and Company Identification

**PRODUCT IDENTIFIER/TRADE/MATERIAL NAME:** Phenobarbital Tablets, USP

**DESCRIPTION:** Phenobarbital Tablets, USP, 16.2 mg, 32.4 mg, 64.8 mg, 97.2 mg

**OTHER DESIGNATIONS:** NDC 13517-110-\*\*, NDC 13517-111-\*\*, NDC 13517-112-\*\*, NDC 13517-113-\*\*.

**IUPAC NAME:** 5-ethyl-5-phenyl-1,3-diazinane-2,4,6-trione.

**CHEMICAL FAMILY:** 5,5-Disubstituted pyrimidinetrione.

**HOW SUPPLIED:** Phenobarbital tablets, USP are available as 16.2 mg tablets, 32.4 mg tablets, 64.8 mg tablets, and 97.2 mg tablets for oral administration.

**FORMULA:**  $C_{12}H_{12}N_2O$  M.W. = 232.24

**PRODUCT USE:** Phenobarbital Tablets are indicated as:

1. Sedative
2. Anticonvulsant – For the treatment of generalized and partial seizures.

**CLASSIFICATION:** Barbiturate.

**MANUFACTURED FOR:**

e5 Pharma, LLC  
225 NE Mizner Blvd, Suite 770  
Boca Raton, FL 33432

**EMERGENCY TELEPHONE NUMBER:** (561) 288-4885



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### Section 2 - Hazards Identification

#### **GLOBAL HARMONIZATION AND EU CLP REGULATION (EC) 1272/2008 LABELING AND**

**CLASSIFICATION:** According to Article 1, item 5 (a) of CLP Regulation (EC) 1272/2008, medicinal products in the finished state for human use, as defined in 2001/83/EC, are excepted from classification and other criteria of 1272/2008.

**EU LABELING/CLASSIFICATION:** According to Article 1 of European Union Council Directive 92/32/EEC, medical products in the finished state for human use (as defined by European Union Council Directives 67/548/EEC and 87/21/EEC) are not subject to the regulations and administrative provisions of European Union Council Directive 92/32/EEC.

#### **EMERGENCY OVERVIEW:**

**Product Description:** This product is supplied as round, white, scored tablets.

**Health Hazards:** No specific health hazards are anticipated from normal handling of this product in the workplace. Therapeutic use of this product may cause sedation, drowsiness, lethargy, vertigo restlessness, excitement, delirium, respiratory depression, apnea, circulatory collapse, nausea and vomiting; and headache.


**Flammability Hazards:** If heated to high temperatures for a prolonged period, the product may ignite. When involved in a fire, this material may decompose and produce irritating vapors and toxic compounds (including carbon oxides, nitrogen oxides, hydrogen chloride gas).

**Reactivity Hazards:** This product is not reactive.

**Environmental Hazards:** Large quantities released to the aquatic and terrestrial environment may have an adverse effect.

**Emergency Considerations:** Emergency responders should wear appropriate protection for the situation to which they respond.

### Section 3 - Composition / Information on Ingredients

CHEMICAL NAME	CAS #	EINECS #	% w/w	LABEL CLASSIFICATION EU Classification (67/548/EEC) GHS & EU Classification (1272/2008 EC) Risk Phrases/Hazard Statements
<b>ACTIVE INGREDIENT(S)</b>				
Phenobarbital	50-06-6	200-007-0	Proprietary	<p><b>Physical hazards</b> Not classified.  <b>Health hazards:</b></p> <ul style="list-style-type: none"> <li>Acute toxicity, oral Category 3</li> <li>Carcinogenicity Category 2</li> <li>Reproductive toxicity Category 2</li> <li>Specific target organ toxicity, single exposure Category 3 narcotic effects</li> </ul> <p><b>Environmental hazards:</b> Not classified.  <b>OSHA defined hazards</b> Not classified.  <b>Label elements</b></p> <div style="text-align: center;">  </div> <p><b>Signal word:</b> Danger</p> <p><b>Hazard statement:</b> Toxic if swallowed. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.</p> <p><b>Precautionary statement Prevention:</b> Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.</p> <p><b>Response:</b> If swallowed: Immediately call a poison center/doctor. Rinse mouth. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell.</p> <p><b>Storage:</b> Store in a well-ventilated place. Keep container tightly closed. Store locked up.</p> <p><b>Disposal:</b> Dispose of contents/container in accordance with local/regional/national/international regulations.</p> <p><b>Hazard(s) not otherwise classified (HNOC):</b> Not classified  <b>Other hazards which do not result in classification:</b> None known.</p>
<b>EXCIPIENTS</b>				
Colloidal Silicon Dioxide	7631-86-9	231-545-4	Proprietary	EU 67/548: Classification: Not applicable. GHS & EU 1272/2008: Classification: Not applicable.
Lactose Anhydrous	63-42-3	200-559-2	Proprietary	EU 67/548: Classification: Not applicable. GHS & EU 1272/2008: Classification: Not applicable.
Magnesium Stearate	557-04-0	209-150-3	Proprietary	EU 67/548: Classification: Not applicable. GHS & EU 1272/2008: Classification: Not applicable.
Microcrystalline Cellulose	9004-34-6	232-674-9	Proprietary	EU 67/548: Classification: Not applicable. GHS & EU 1272/2008: Classification: Not applicable.
Sodium Starch Glycolate	9063-38-1	618-597-7	Proprietary	EU 67/548: Classification: Not applicable. GHS & EU 1272/2008: Classification: Not applicable.
Stearic Acid	57-11-4	200-313-4	Proprietary	EU 67/548: Classification: Not applicable. GHS & EU 1272/2008: Classification: Not applicable.



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### Section 4 - First Aid Measures

**DESCRIPTION OF FIRST AID MEASURES:** Contaminated individuals must be taken for medical attention if any adverse effects occur. Remove contaminated clothing and shoes. Take a copy of this SDS to health professional with victim. Wash clothing and thoroughly clean shoes before reuse.

**SKIN EXPOSURE:** No specific effect is expected from skin contact. If this product contaminates the skin and adverse effect occurs, begin decontamination with running water. The contaminated individual must seek medical attention if any adverse effects occur after flushing.

**EYE EXPOSURE:** If dusts from product enter the eyes, open contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have contaminated individual "roll" eyes. Minimum flushing is for 20 minutes. Contaminated individual must seek medical attention if adverse effect continues after flushing.

**INHALATION:** If dusts of this product are inhaled, remove victim to fresh air. The contaminated individual must seek medical attention if any adverse effects occur.

**INGESTION:** This product is intended to be swallowed; however, if an overdose occurs **CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION.** If professional advice is not available, seek immediate medical attention. If alert, victim should drink up to three glasses of water. Do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If victim is convulsing, maintain an open airway and obtain emergency medical attention.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Phenobarbital can cause fetal harm when administered to a pregnant woman. Barbiturates readily cross the placental barrier and are distributed throughout fetal tissues; the highest concentrations are found in the placenta, fetal liver, and brain.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT IF NEEDED:** Treat symptoms and eliminate exposure. Persons developing hypersensitivity reactions should receive medical attention.

**Section 5 - Fire Fighting Measures**

**FLASH POINT:** Not available.

**AUTOIGNITION TEMPERATURE:** Not available.

**FLAMMABLE LIMITS** (in air by volume, %): Not applicable.

**FIRE EXTINGUISHING MEDIA:** Unless incompatibilities exist for surrounding materials, carbon dioxide, water spray, 'ABC' type chemical extinguishers, foam, dry chemical and halon extinguishers can be used to fight fires involving this product.


**UNSUITABLE FIRE EXTINGUISHING MEDIA:** None known.

**SPECIAL HAZARDS ARISING FROM THE SUBSTANCE:** This product must be substantially pre-heated before ignition can occur. When involved in a fire, this material may decompose and produce irritating vapors and toxic compounds (including carbon, iron, titanium, sulfur and nitrogen oxides hydrogen chloride gas).

**Explosion Sensitivity to Mechanical Impact:** Not applicable.

**Explosion Sensitivity to Static Discharge:** Not sensitive.

**SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS:** Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. All personal protective gear and contaminated fire-response equipment should be decontaminated with soapy water and thoroughly rinsed before being returned to service. Move fire-exposed containers if it can be done without risk to firefighters. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

**Section 6 - Accidental Release Measures**

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Spill kits, clearly labeled, should be kept in or near preparation and operational areas. It is suggested that kits include a respirator, chemical splash goggles, two pairs of gloves, two sheets (12" x 12") of absorbent material, 250-mL and 1-liter spill control pillows, a small scoop to collect glass fragments (if applicable) and two large waste disposal bags. Absorbents should be able to be incinerated. Avoid generating airborne dusts of this material during spill response procedures as described below.

**PROTECTIVE EQUIPMENT:**

**Small Spills/Spills in Hoods:** Personnel wearing nitrile or other appropriate gloves, lab coat or other protective clothing and eye protection should immediately clean incidental spills of less than 5 g.

**Large Spills:** Use proper protective equipment, including double nitrile or appropriate gloves and protective clothing (i.e., disposable Tyvek coveralls). When there is any danger of airborne dusts being generated, use a full-face respirator equipped with a High Efficiency Particulate (HEPA) filter. Self-Contained Breathing Apparatus (SCBA) can be used instead of an air-purifying respirator.

**METHODS FOR CLEAN-UP AND CONTAINMENT:**

Cleanup of Small Spills: Solids should be gently covered with wet absorbent pads. Clean spill with pad and dispose of properly. Decontaminate the spill area (three times) using a bleach and detergent solution and then rinse with clean water.



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

**Spills in Hoods:** Decontamination of all interior hood surfaces may be required after the above procedures have been followed. If the HEPA filter of a hood is contaminated, label the unit "Do not use-contaminated" and have trained personnel wearing appropriate protective equipment change and dispose of the filter properly as soon as possible.

**Large Spills:** Restrict access to the spill areas. For spills of greater than 5 g, be sure not to generate dusts by gently covering with damp absorbent sheets, spill-control pads, pillows, cloths, or towels. The dispersion of particles into surrounding air and the possibility of inhalation is a serious matter and should be treated as such. Do not apply chemical in-activators as they may produce hazardous by-products. Thoroughly clean all contaminated surfaces three times using a bleach and detergent solution and then rinse with clean water.

**All Spills:** Use procedures described above and then place all spill residues in an appropriate, labeled container and seal. Move to a secure area. Dispose of in accordance with Federal, State, and local hazardous waste disposal regulations (see Section 13, Disposal Considerations). For spills on water, contain, minimize dispersion and collect. Dispose of recovered material and report spill per regulatory requirements.

**ENVIRONMENTAL PRECAUTIONS:** Prevent material from entering sewer or confined spaces, waterways, soil or public waters. Do not flush to sewer. For spills on water, contain, minimize dispersion and collect.

**REFERENCE TO OTHER SECTIONS:** Review Sections 2, 8, 11, & 12 before proceeding with cleanup. See Section 13, Disposal Considerations for more information.

### Section 7 - Handling and Storage

**PRECAUTIONS FOR SAFE HANDLING:** All employees who handle this material should be thoroughly trained to handle it safely. As with all chemicals, avoid getting this material ON YOU or IN YOU. Do not eat or drink while handling this material. After handling this material, wash face and hands thoroughly prior to eating, drinking, smoking or applying cosmetics. Ensure this material is used with adequate ventilation. Appropriate personal protective equipment must be worn (see Section 8, Exposure Controls - Personal Protection). Open containers slowly on a stable surface in areas that have been designated for use of this material. Minimize all exposures to this material. Avoid generation of dusts. Areas in which this material is used should be wiped down, so that this material does not accumulate.

**CONDITIONS FOR SAFE STORAGE:** Containers of this material must be properly labeled. Store containers in a cool, dry location, away from direct sunlight and sources of intense heat. Recommended Storage Temperature: 20-25 °C (68-77 °F). Store away from incompatible materials (see Section 10, Stability and Reactivity). Material should be stored in secondary containers. Keep containers tightly closed when not in use. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. Have appropriate extinguishing equipment in the storage area (e.g., sprinkler system, portable fire extinguishers). Empty containers may contain residual material; therefore, empty containers should be handled with care and disposed of properly.

**SPECIFIC END USE(S):** This product is a human pharmaceutical.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** When cleaning non-disposable equipment, wear nitrile or other appropriate gloves (double gloving is recommended), goggles, and lab coat. Prevent dispersion of particulates by wetting or dampening surfaces prior to clean up of equipment. If applicable, wash equipment using a bleach and detergent solution and then rinse with clean water.



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### Section 8 - Exposure Controls / Personal Protection

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR							
		ACGIH-TLVs		OSHA-PELs		NIOSH-RELS		NIOSH	OTHER
		TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	IDLH mg/m <sup>3</sup>	mg/m <sup>3</sup>
Phenobarbital	50-06-6	NE	NE	NE	NE	NE	NE	NE	NE
Colloidal Silicon Dioxide	7631-86-9	NE	NE	NE	NE	6 mg/m <sup>3</sup>	NE	NE	NE
Lactose Anhydrous	63-42-3	NE	NE	NE	NE	NE	NE	NE	NE
Magnesium Stearate Exposure limits are for stearates	557-04-0	10	NE	NE	NE	NE	NE	NE	Carcinogen: TLV-A4
Microcrystalline Cellulose	9004-34-6	10	NE	15 (total dust), 5 (resp. fraction)	NE	10 (total dust), 5 (resp. fraction)	NE	NE	NE
Sodium Starch Glycolate	9063-38-1	NE	NE	NE	NE	NE	NE	NE	NE
Stearic Acid	57-11-4	NE	NE	NE	NE	NE	NE	NE	NE

NE = Not Established. See Section 16 for Definitions of Terms Used.

**INTERNATIONAL OCCUPATIONAL EXPOSURE LIMITS:** In addition to the exposure limit values cited in this section, other exposure limits have been established by various countries for the components of this product. Below are available limits for the active ingredient and excipient components. The exposure limits given may not be the most current; individual country authorities should be contacted to check on more current limits.

**MAGNESIUM STEARATE:**

New Zealand: TWA = 10 mg/m<sup>3</sup> (inspirable dust), JAN 2002  
Sweden: TWA = 5 mg/m<sup>3</sup>, JUN 2005

The Netherlands: MAC-TGG = 2 mg/m<sup>3</sup>, 2003

New Zealand: TWA = 10 mg/m<sup>3</sup> (inspirable dust), JAN 2002

Russia: STEL = 10 mg/m<sup>3</sup>, JUN 2003

Switzerland: MAK-W = W 6 mg/m<sup>3</sup>, DEC 2006

United Kingdom: TWA = 10 mg/m<sup>3</sup> (inhalable), 2005

United Kingdom: TWA = 4 mg/m<sup>3</sup>; STEL = 20 mg/m<sup>3</sup> (respirable), 2005

In Argentina, Bulgaria, Colombia, Jordan, Singapore, Vietnam, check ACGIH TLV

**MICROCRYSTALLINE CELLULOSE:**

Belgium: TWA = 10 mg/m<sup>3</sup>, MAR 2002

France: VME = 10 mg/m<sup>3</sup>, FEB 2006

Korea: TWA = 10 mg/m<sup>3</sup>, 2006

Mexico: TWA = 10 mg/m<sup>3</sup>; STEL = 20 mg/m<sup>3</sup>, 2004





## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### PROTECTIVE EQUIPMENT:

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), equivalent standards of Canada (including CSA Standard Z94.4-02 and CSA Standard Z94.3-02), standards of EU member states (including EN 529:2005 for respiratory PPE, CEN/TR 15419:2006 for hand protection, and CR 13464:1999 for face/eye protection). Please reference applicable regulations and standards for relevant details.

**RESPIRATORY PROTECTION:** Respiratory protection is generally not needed during routine conditions of use of this product. If respiratory protection is needed, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-02, or the European Standard EN 529:2005, and EU member state standards. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary Self-Contained Air Supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

**EYE PROTECTION:** Eye protection is not normally needed during medical administration of this product. During operations in which dusts of the product may be generated, splash goggles or safety glasses should be considered. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian CSA Standard Z94.3-07, the European Standard CR 13464:1999, or EU member states standards.

**HAND PROTECTION:** During medical administration of this product, medical latex or nitrile gloves should be worn to avoid absorption of the product. During manufacture or other similar industrial operations, wear the appropriate hand protection for the process. Use double gloves for spill response, as stated in Section 6 (Accidental Release Measures) of this SDS. If necessary, refer to U.S. OSHA 29 CFR 1910.138, appropriate Standards of Canada, the European Standard CEN/TR 15419:2006, or EU member states standards.

**BODY PROTECTION:** Use appropriate protective clothing for the task (e.g., lab coat, etc.) If necessary, refer to the OSHA Technical Manual (Section VII: Personal Protective Equipment), appropriate Standards of Canada, or the European Standard CEN/TR 15419:2006.

### Section 9 - Physical & Chemical Properties

The following information is for the product as a whole.

Appearance:	Round, white, scored	Odor:	N/A
Physical State:	Tablet	pH:	N/A
Vapor Pressure:	N/A	Vapor Density:	N/A
Boiling Point:	N/A	Melting Point:	Unknown
Solubility (H <sub>2</sub> O):	Soluble	Specific Gravity:	Unknown
Evaporation Rate:	N/A	VOC:	Unknown
Octanol/H <sub>2</sub> O Coeff.:	N/A	Flash Point:	Unknown
Flash Point Method:	N/A	Upper Flammability Limit (UFL):	Unknown
Lower Flammability Limit (LFL):	N/A	Burning Rate:	Unknown
Auto Ignition:	N/A		



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

The following information is for the active ingredient phenobarbital.

Appearance	: Colorless crystals or white crystalline powder.
Physical State	: Solid
Odor	: Odorless
pH	: 5 (saturated solution).
Melting point/freezing point	: 345.2 - 352.4 °F (174 - 178 °C)
Initial boiling point and boiling range	: Not available.
Flash point	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 0.0000001 kPa at 25 °C
Vapor density	: Not available.
Relative density	: Not available.
Solubility in water	: Very slightly soluble.
Partition coefficient (n-octanol/water)	: 1.47
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.

### Section 10 - Chemical Stability & Reactivity Information

**REACTIVITY/CHEMICAL STABILITY:** This product is not reactive.

**DECOMPOSITION PRODUCTS:** *Combustion:* If exposed to extremely high temperatures, the products of thermal decomposition may include irritating fumes and toxic gases (e.g., carbon oxides, nitrogen oxides, sodium oxides, magnesium oxides, and hydrogen chloride). *Hydrolysis:* None known.

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** This product is generally compatible with other common materials in a medical facility. Acids and alkalies, and other chemicals that could affect its performance should be avoided.

**POSSIBILITY HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid heat, light, and contact with incompatible chemicals.

### Section 11 - Toxicological Information

**SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE:** The health hazard information provided below is pertinent to medical employees using this product in an occupational setting. The following paragraphs describe the symptoms of exposure by route of exposure.

**INHALATION:** Inhalation of airborne dusts generated by this product may slightly irritate the nose, throat, and lungs. Symptoms are generally alleviated upon breathing fresh air.

**CONTACT WITH SKIN or EYES:** Contact with the skin may cause mild irritation, which is alleviated upon rinsing. Prolonged or repeated skin contact may cause dermatitis (dry, red skin). Contact with the eyes of airborne dusts generated by damaged tablets of this product may cause mild to moderate irritation, redness, and tearing.

**SKIN ABSORPTION:** The components of this product are not known to be absorbed through intact skin.

**INGESTION:** Ingestion is not a significant route of occupational overexposure. Symptoms of prolonged or repeated ingestion, as may occur when poor industrial hygiene is practiced, may include those described for "Other Potential Health Effects". Individuals who have had allergic reactions to products containing phenobarbital, or any of the other ingredients in this product may experience allergic reactions to this product. Rarely, allergic-type skin rashes, petechiae, or ecchymoses may develop during treatment. Angioneurotic edema or anaphylactic reactions are extremely rare.

**INJECTION:** Though not anticipated to be a significant route of overexposure for this product, injection (via punctures or lacerations by contaminated objects) may cause redness at the site of injection. Symptoms from prolonged or repeated exposure may include those described for "Other Potential Health Effects".



**SYMPTOMS OF EXPOSURE BY ROUTE OF EXPOSURE:** The main route of occupational exposure to this product is via inhalation of dusts and skin contact. The anticipated symptoms of exposure, by route of exposure are described further in this section.

**INHALATION:** Inhalation of airborne dusts generated by damaged capsules of this product may slightly irritate the nose, throat, and lungs. In addition, inhalation may result in adverse effects as described under 'Other Potential Health Effects'.

**CONTACT WITH SKIN or EYES:** It is anticipated that this product may irritate contaminated skin or eyes. Symptoms of skin contact may include itching and redness. Symptoms of eye contact can include redness, pain, and watering (mechanical irritation).

**SKIN ABSORPTION:** No data is available on potential absorption of this material through intact skin.

**INGESTION:** Ingestion of this product (i.e., through poor hygiene practices) may be harmful or toxic by ingestion. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Other effects may occur as described under 'Other Potential Health Effects'.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
<b>HEALTH HAZARD</b>	(BLUE)	1	
<b>FLAMMABILITY HAZARD</b>	(RED)	0	
<b>PHYSICAL HAZARD</b>	(YELLOW)	0	
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate  
3 = Serious 4 = Severe \* = Chronic hazard



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

**INJECTION:** Not a potential route of exposure for tablets.

### OTHER POTENTIAL HEALTH EFFECTS:

*Nervous System:* Agitation, confusion, hyperkinesia, ataxia, CNS depression, nightmares, nervousness, psychiatric disturbance, hallucinations, insomnia, anxiety, dizziness, abnormality in thinking

*Respiratory System:* Hypoventilation, apnea

*Cardiovascular System:* Bradycardia, hypotension, syncope

*Digestive System:* Nausea, vomiting, constipation

*Other Reported Reactions:* Headache, hypersensitivity reactions (angioedema, skin rashes, exfoliative dermatitis), fever, liver damage, megaloblastic anemia following chronic phenobarbital use.

### HEALTH EFFECTS OR RISKS FROM EXPOSURE:

**Acute:** Dusts from product may cause irritation if inhaled and in contact with skin or eyes. Accidental ingestion may be harmful or cause toxic effects. Acute exposure may cause effects described in "Other Potential Health Effects".

**Chronic:** Chronic exposure may lead to symptoms described under 'Other Potential Health Effects'. May cause harm to fetus. No chronic effects have been reported from workplace exposure.

**TARGET ORGANS:** It is anticipated that for Occupational Exposure the target organs are: Acute: Skin, eyes, respiratory system. Chronic: None reported. In therapeutic use, this product may have an impact on the body systems listed under 'Other Potential Health Effects'.

## Section 12 - Ecological Information

**ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.**

**MOBILITY:** This product has not been tested for mobility in soils. No predicted values are available.

**PERSISTENCE AND BIODEGRADABILITY:** This product has not been tested for persistence and biodegradability. No predicted values are available.

**BIO-ACCUMULATION POTENTIAL:** This product has not been tested for bio-accumulation potential.

**ECOTOXICITY:** At high levels, this product may be harmful or fatal to contaminated plant and animal-life (especially if large quantities are released). This product has not been tested for aquatic toxicity. No aquatic toxicity data are available for components of this product.

**OTHER ADVERSE EFFECTS:** The components of this product are not listed as having ozone depletion potential.

**ENVIRONMENTAL EXPOSURE CONTROLS:** Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

## Section 13 - Disposal Considerations

**WASTE TREATMENT/DISPOSAL METHODS:** Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. All protective clothing, gloves, and disposable materials used in the manufacture or handling of this drug should be disposed of in accordance with established hazardous waste disposal procedures. It is the responsibility of the generator to



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

determine at the time of disposal whether the product meets the criteria of a hazardous waste per regulations of the area in which the waste is generated and/or disposed. Incineration or other approved methods of disposal are recommended for the product and disposable equipment. Shipment of wastes must be done with appropriately permitted and registered transporters. Reusable equipment should be cleaned with soap and water and thoroughly rinsed.

**DISPOSAL CONTAINERS:** Unless the waste is going to an approved landfill, the waste materials must be placed in and shipped in appropriate 5-gallon or 55-gallon poly or metal waste pails or drums. Permeable cardboard containers are not appropriate and should not be used. Ensure that any required marking or labeling of the containers be done to all applicable regulations.

**PRECAUTIONS TO BE FOLLOWED DURING WASTE HANDLING:** Wear proper protective equipment when handling waste materials.

**U.S. EPA WASTE NUMBER:** Not applicable.

**EWG WASTE CODE:** Wastes from Human or Animal Health Care or Related Research: 18 01 09: Medicines Other Than Those Mentioned in 18 01 08.

### Section 14 - Transportation Information

**U.S. DEPARTMENT OF TRANSPORTATION REGULATIONS:** This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

**TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:** This product is not classified as Dangerous Goods, per regulations of Transport Canada.

**INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):** This product is not classified as Dangerous Goods, by rules of IATA.

**INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:** This product is not classified as Dangerous Goods by the International Maritime Organization.

**EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):** This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

### Section 15 - Regulatory Information

#### UNITED STATES REGULATIONS:

**U.S. SARA REPORTING REQUIREMENTS:** The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

**U.S. SARA THRESHOLD PLANNING QUANTITY:** There are no specific Threshold Planning Quantities for any component of this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lbs. (4,540 kg) therefore applies, per 40 CFR 370.20.

**U.S. CERCLA REPORTABLE QUANTITIES (RQ):** Not applicable.

**U.S. TSCA INVENTORY STATUS:** This product is regulated under Food and Drug Administration standards; it is not subject to requirements under TSCA.





## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

**CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):** No component of this product is on the California Proposition 65 Lists. US Federal Regulations

### **CANADIAN REGULATIONS:**

**CANADIAN DSL INVENTORY STATUS:** This product is regulated by the Therapeutic Products Program (TPP) of Health Canada; it is exempt from the requirements of CEPA.

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:** The components of this product are not on the CEPA Priorities Substances Lists.

**CANADIAN WHMIS CLASSIFICATION AND SYMBOL:** The WHMIS Requirements of the Hazardous Products Act does not apply in respect of the advertising, sale or importation of any cosmetic, device, drug or food within the meaning of the Food and Drugs Act.

### **EUROPEAN COMMUNITY REGULATIONS:**

**SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE PRODUCT:** When formulated in a finished medicinal product for human use, this material is subject to Directive 2001/83/EC and subsequent amendments to the directive.

**CHEMICAL SAFETY ASSESSMENT:** No Data Available. The chemical safety assessment is required for some substances according to European Union Regulation (EC) 1907/2006, Article 14.

### **Section 16 - Other Information**

**EU CLP REGULATION (EC) 1272/2008 LABELING AND CLASSIFICATION:** According to Article 1, item 5 (a) of CLP Regulation (EC) 1272/2008, medicinal products in the finished state for human use, as defined in 2001/83/EC, are exempted from classification and other criteria of 1272/2008.

**EU LABELING AND CLASSIFICATION 67/548/EEC:** According to Article 1 of European Union Council Directive 92/32/EEC, medical products in the finished state for human use (as defined by European Union Council Directives 67/548/EEC and 87/21/EEC) are not subject to the regulations and administrative provisions of European Union Council Directive 92/32/EEC.

**REFERENCES AND DATA SOURCES:** Contact the supplier for information.

**METHODS OF EVALUATING INFORMATION FOR THE PURPOSE OF CLASSIFICATION:** Bridging principles were used to classify this product.

**REVISION DETAILS:** Revision Date: 02/12/2020



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### DEFINITION OF TERMS

For information on medical terms used in this SDS consult an on-line database such as Medline Plus:

<http://www.nlm.nih.gov/medlineplus/druginformation.html>.

A large number of abbreviations and acronyms appear on a SDS. Some of these, which are commonly used, include the following:

#### EXPOSURE LIMITS IN AIR:

**CAS #:** This is the Chemical Abstract Service Number that uniquely identifies each constituent.

**CEILING LEVEL:** The concentration that shall not be exceeded during any part of the working exposure.

**ACGIH** - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits. **TLV** - Threshold Limit Value - an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (**TWA**), the 15-minute Short Term Exposure Limit, and the instantaneous Ceiling Level (**C**). Skin absorption effects must also be considered.

**DFG MAK Germ Cell Mutagen Categories:** **1:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances which have been shown to induce genetic damage in germ cells of human or animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances which are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but which are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

**DFG MAK Pregnancy Risk Group Classification: Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

**IDLH-Immediately Dangerous to Life and Health:** This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

**LOQ:** Limit of Quantitation.

#### EXPOSURE LIMITS IN AIR (continued):

**DFG MAK Pregnancy Risk Group Classification: Group A: (continued):**

**MAK:** Federal Republic of Germany Maximum Concentration Values in the workplace.

**NE:** Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

**NIC:** Notice of Intended Change.

**NIOSH CEILING:** The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

**NIOSH RELs:** NIOSH's Recommended Exposure Limits.

**PEL-Permissible Exposure Limit:** OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

**SKIN:** Used when there is a danger of cutaneous absorption.

**STEL-Short Term Exposure Limit:** Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

**TLV-Threshold Limit Value:** An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

**TWA-Time Weighted Average:** Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

**HAZARD RATINGS:** This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

**HEALTH HAZARD: 0 (Minimal Hazard):** No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. PII or Draize = "0". *Eye Irritation:* Essentially non-irritating, or minimal effects which clear in < 24 hours [e.g. mechanical irritation]. Draize = "0". *Oral Toxicity LD<sub>50</sub> Rat:* < 5000 mg/kg. *Dermal Toxicity LD<sub>50</sub> Rat or Rabbit:* < 2000 mg/kg. *Inhalation Toxicity 4-hrs LC<sub>50</sub> Rat:* < 20 mg/L; **1 (Slight Hazard):** Minor reversible injury may occur; slightly or mildly irritating. *Skin Irritation:* Slightly or mildly irritating. *Eye Irritation:* Slightly or mildly irritating. *Oral Toxicity LD<sub>50</sub> Rat:* > 500-5000 mg/kg. *Dermal Toxicity LD<sub>50</sub> Rat or Rabbit:* > 1000-2000 mg/kg. *Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat:* > 2-20 mg/L; **2 (Moderate Hazard):** Temporary or transitory injury may occur. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. PII or Draize > 0, < 5. *Eye Irritation:* Moderately to severely irritating and/or corrosive; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. Draize > 0, < 25. *Oral Toxicity LD<sub>50</sub> Rat:* > 50-500 mg/kg. *Dermal Toxicity LD<sub>50</sub> Rat or Rabbit:* > 200-1000 mg/kg. *Inhalation Toxicity LC<sub>50</sub>*

**HAZARDOUS MATERIALS IDENTIFICATION SYSTEM****HAZARD RATINGS (continued):****HEALTH HAZARD (continued):**

4-hrs Rat. > 0.5-2 mg/L.; **3** (Serious Hazard: Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may destroy dermal tissue, cause skin burns, dermal necrosis. PII or Draize > 5-8 with destruction of tissue. *Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. *Oral Toxicity LD<sub>50</sub> Rat.* > 1-50 mg/kg. *Dermal Toxicity LD<sub>50</sub> Rat or Rabbit.* > 20-200 mg/kg. *Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat.* > 0.05-0.5 mg/L.; **4** (Severe Hazard: Life-threatening; major or permanent damage may result from single or repeated exposure. *Skin Irritation:* Not appropriate. Do not rate as a "4", based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a "4", based on eye irritation alone. *Oral Toxicity LD<sub>50</sub> Rat.* < 1 mg/kg. *Dermal Toxicity LD<sub>50</sub> Rat or Rabbit.* < 20 mg/kg. *Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat.* < 0.05 mg/L.)

**FLAMMABILITY HAZARD: 0** (Minimal Hazard-Materials that will not burn in air when exposure to a temperature of 815.5°C [1500°F] for a period of 5 minutes.); **1** (Slight Hazard-Materials that must be pre-heated before ignition can occur. Material require considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur, Including:

Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C [200°F] (e.g. OSHA Class IIIB, or; Most ordinary combustible materials [e.g. wood, paper, etc.]; **2** (Moderate Hazard-Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres in air, Including: Liquids having a flash-point at or above 37.8°C [100°F]; Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp; Solids and semisolids that readily give off flammable vapors.); **3** (Serious Hazard- Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions, including: Liquids having a flash point below 22.8°C [73°F] and having a boiling point at or above 38°C [100°F] and below 37.8°C [100°F] [e.g. OSHA Class IB and IC]; Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air [e.g., dusts of combustible solids, mists or droplets of flammable liquids]; Materials that burn extremely rapidly, usually by reason of self-contained oxygen [e.g. dry nitrocellulose and many organic peroxides]); **4** (Severe Hazard-Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and which will burn readily, including: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C [73°F] and a boiling point below 37.8°C [100°F] [e.g. OSHA Class IA; Material that ignite spontaneously when exposed to air at a temperature of 54.4°C [130°F] or below [e.g. pyrophoric]).

**PHYSICAL HAZARD: 0** (*Water Reactivity:* Materials that do not react with water. *Organic Peroxides:* Materials that are normally stable, even

**HAZARDOUS MATERIALS IDENTIFICATION SYSTEM****HAZARD RATINGS (continued):****PHYSICAL HAZARD (continued):**

under fire conditions and will not react with water. *Explosives:* Substances that are Non-Explosive. *Unstable Compressed Gases:* No Rating. *Pyrophorics:* No Rating. *Oxidizers:* No "0" rating allowed. *Unstable Reactives:* Substances that will not polymerize, decompose, condense or self-react.); **1** (*Water Reactivity:* Materials that change or decompose upon exposure to moisture. *Organic Peroxides:* Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy. *Explosives:* Division 1.5 & 1.6 substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases:* Pressure below OSHA definition. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group III; **Solids:** any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. **Liquids:** any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives:* Substances that may decompose, condense or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosive hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors.); **2** *Water Reactivity:* Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 – Explosive substances where the explosive effect are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group II **Solids:** any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. **Liquids:** any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature); **3** (*Water Reactivity:* Materials that may form explosive reactions with water. *Organic Peroxides:* Materials that are capable of detonation or explosive reaction, but require a strong initiating source, or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives:* Division 1.2 – Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases:* Pressure > 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group I **Solids:** any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3.:2 potassium bromate/cellulose mixture. **Liquids:** Any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives:* Substances that may polymerize, decompose,





## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

#### HAZARD RATINGS (continued):

##### PHYSICAL HAZARD (continued):

condense or self-react at ambient temperature and/or pressure and have a moderate potential to cause significant heat generation or explosion.); **4** (*Water Reactivity*: Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides*: Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives*: Division 1.1 & 1.2-explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases*: No Rating. *Pyrophorics*: Add to the definition of Flammability "4". *Oxidizers*: No "4" rating. *Unstable Reactives*: Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a high potential to cause significant heat generation or explosion).

#### NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials. Gases and vapors with an LC<sub>50</sub> for acute inhalation toxicity greater than 10,000 ppm. Dusts and mists with an LC<sub>50</sub> for acute inhalation toxicity greater than 200 mg/L. Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 2000 mg/kg. Materials with an LD<sub>50</sub> for acute oral toxicity greater than 2000 mg/kg. Materials essentially non-irritating to the respiratory tract, eyes, and skin. **1** Materials that, under emergency conditions, can cause significant irritation. Gases and vapors with an LC<sub>50</sub> for acute inhalation toxicity greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists with an LC<sub>50</sub> for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L. Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD<sub>50</sub> for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg.

Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. Gases with an LC<sub>50</sub> for acute inhalation toxicity greater than 3,000 ppm but less than or equal to 5,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC<sub>50</sub> for acute inhalation toxicity, if its LC<sub>50</sub> is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Dusts and mists with an LC<sub>50</sub> for acute inhalation toxicity greater than 2 mg/L but less than or equal to 10 mg/L. Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 200 mg/kg but less than or equal to 1000 mg/kg. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lachrymators. Materials that are primary skin irritants or sensitizers. Materials whose LD<sub>50</sub> for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. Dusts and mists with an LC<sub>50</sub> for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L. Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD<sub>50</sub> for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg. **3** (materials that, under emergency conditions, can cause serious or permanent injury): Gases and vapors whose LC<sub>50</sub> for acute inhalation toxicity is greater than

### NATIONAL FIRE PROTECTION ASSOCIATION

#### HAZARD RATINGS (continued):

##### HEALTH HAZARD (continued):

1,000 ppm but less than or equal to 3,000 ppm. Dusts and mists whose LC<sub>50</sub> for acute inhalation toxicity is greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials whose LD<sub>50</sub> for acute dermal toxicity is greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials whose LD<sub>50</sub> for acute oral toxicity is greater than 5 mg/kg but less than or equal to 50 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC<sub>50</sub> for acute inhalation toxicity, if its LC<sub>50</sub> is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials that are respiratory irritants. Cryogenic gases that cause frostbite and irreversible tissue damage. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials that are corrosive to the skin. **4** (materials that, under emergency conditions, can be lethal): Gases and vapors whose LC<sub>50</sub> for acute inhalation toxicity less than or equal to 1,000 ppm. Dusts and mists whose LC<sub>50</sub> for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD<sub>50</sub> for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD<sub>50</sub> for acute oral toxicity is less than or equal to 5 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC<sub>50</sub> for acute inhalation toxicity, if its LC<sub>50</sub> is less than or equal to 1000 ppm.

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand: Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur: Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. Liquids, solids and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the *Method of Testing for Sustained Combustibility*, per 49 CFR 173, Appendix H or the UN *Recommendation on the Transport of Dangerous Goods, Model Regulations* (current edition) and the related *Manual of Tests and Criteria* (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85 percent by weight. Liquids that have no fire point when tested by ASTM D 92 Standard Test Method for Flash and Fire Points by Cleveland Open Cup, up to a boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed up flash point of the solvent. Most ordinary combustible materials. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air: Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### NATIONAL FIRE PROTECTION ASSOCIATION

#### HAZARD RATINGS (continued):

##### FLAMMABILITY HAZARD (continued):

but that generally do not form explosive mixtures in air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that, on account of their physical form or environmental conditions, can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with a representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily: Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air, Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: **0** Materials that in themselves are normally stable, even under fire conditions: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL.

Materials that readily undergo violent chemical change at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures.

#### FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). Flash Point - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Auto ignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

#### TOXICOLOGICAL INFORMATION:

**Human and Animal Toxicology:** Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD<sub>50</sub>** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC<sub>50</sub>** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m<sup>3</sup>** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Sub rankings (2A, 2B, etc.) are also used. **Other Information:** **BEI** - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

#### REPRODUCTIVE TOXICITY INFORMATION:

##### **REPRODUCTIVE TOXICITY INFORMATION:**

A **mutagen** is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An **embryotoxin** is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance which interferes in any way with the reproductive process.

##### **United States FDA Pharmaceutical Pregnancy Categories:**

**Pregnancy Category A:** Adequate and well-controlled human studies have failed to demonstrate a risk to the fetus in the first trimester of pregnancy (and there is no evidence of risk in later trimesters).

**Pregnancy Category B:** Animal reproduction studies have failed to demonstrate a risk to the fetus and there are no adequate and well-controlled studies in pregnant women OR Animal studies have shown an adverse effect, but adequate and well-controlled studies in pregnant women have failed to demonstrate a risk to the fetus in any trimester.

**Pregnancy Category C:** Animal reproduction studies have shown an adverse effect on the fetus and there are no adequate and well-controlled studies in humans, but potential benefits may warrant use of the drug in pregnant women despite potential risks. **Pregnancy Category D:** There is positive evidence of human fetal risk based on adverse reaction data from investigational or marketing experience or studies in humans, but potential benefits may warrant use of the drug in pregnant women despite potential risks. **Pregnancy Category X:** Studies in animals or humans have demonstrated fetal abnormalities



## Safety Data Sheet

Preparation Date: 10/17/2016

Revision Date: 02/12/2020

Revision Number: 02

### REPRODUCTIVE TOXICITY INFORMATION

#### (continued):

and/or there is positive evidence of human fetal risk based on adverse reaction data from investigational or marketing experience, and the risks involved in use of the drug in pregnant women clearly outweigh potential benefits. **Pregnancy Category N:** FDA has not classified this drug.

### ECOLOGICAL INFORMATION:

EC is the effect concentration in water. **BCF** = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter. **TL<sub>m</sub>** = median threshold limit; Coefficient of Oil/Water Distribution is represented by **log K<sub>ow</sub>** or **log K<sub>oc</sub>** and is used to assess a substance's behavior in the environment.

### REGULATORY INFORMATION:

#### U.S. and CANADA:

**ACGIH:** American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits. This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings which appear on the material's package label. **OSHA** - U.S. Occupational Safety and Health Administration.

#### EUROPEAN and INTERNATIONAL:

**The DFG:** This is the Federal Republic of Germany's Occupation Health Agency, similar to the U.S. OSHA. **EU** is the European Community (formerly known as the EEC, European Economic Community). **EINECS:** This is the European Inventory of Now-Existing Chemical Substances. The **ARD** is the European Agreement Concerning the International Carriage of Dangerous Goods by Road and the **RID** are the International Regulations Concerning the Carriage of Dangerous Goods